

DFS型 干燥过滤筒
Model DFS Replaceable Dry Filter Cartridge

- DFS型干燥过滤筒安装在系统的液、汽管路中，可有效去除残留的污染物，从而使压缩机得到更好的保护，延长其使用寿命。
- DFS型干燥过滤筒是可更换滤芯的，最大的特点是用于吸附压缩机马达烧毁后进入系统中大量的水分。
- Model DFS dry filter cartridge is installed on the liquid and vapor piping, which could effectively remove any residual contaminant to protect compressor for a longer service life.
- The filter element of Model DFS dry filter cartridge is replaceable and it is capable to absorb large amount of water in the system in case the compressor motor burns up.



特点 Features

- 可拆式结构、便于安装及维修；
- 100目出口滤网；
- 全流通设计，最大限度的减少压降；
- 钢制壳体，铜接管焊接口，高频焊接采用翻边结构，增加焊接可靠性；
- 改性聚四氟乙烯新型材料，确保密封性；
- 外涂层采用环氧树脂静电喷漆。

- Removable structure for convenient installation and maintenance；
- 100 mesh outlet filter screen；
- Full pass through design to minimize pressure drop；
- Steel casing, copper pipe welded connection, high frequency welding flanging structure to improve welding reliability；
- Modified Teflon new material to ensure perfect sealing；
- Outer surface applies epoxy resin coating protection.

认 证 Certification ● ISO 9001 ● CE ● QS

技术参数 Technical Parameters

适用制冷剂 Suitable Refrigerants	HCFC、HFC、CFC
适用介质温度 Suitable Medium Temperature	-35℃~+70℃
最大工作压力 Maximum Working Pressure	4.2Mpa
最小爆破压力 Minimum Bursting Pressure	18.9MPa

造型 Selection

型号 Type	进出口尺寸 Connections To solder ID Finch	芯体数量 Number of cores	过滤面积 Filtering surface(m ²)	尺寸 Dimensions(mm)		
				A	B	C
DFS-485S	5/8 ODF	1	420	234	153	85
DFS-486S	3/4 ODF			234	153	85
DFS-487S	7/8 ODF			234	153	85
DFS-489S	1-1/8 ODF			236	155	87
DFS-4811S	1-3/8 ODF			240	159	91
DFS-4813S	1-5/8 ODF			242	161	93
DFS-4817S	2-1/8 ODF			246	160	99
DFS-4821S	2-5/8 ODF			244	158	106
DFS-967S	7/8 ODF	2	840	376	295	85
DFS-969S	1-1/8 ODF			378	297	87
DFS-9611S	1-3/8 ODF			382	301	91
DFS-9613S	1-5/8 ODF			384	303	93
DFS-9617S	2-1/8 ODF			388	302	99
DFS-9621S	2-5/8 ODF			386	300	106
DFS-1449S	1-1/8 ODF	3	1260	520	439	87
DFS-14411S	1-3/8 ODF			524	443	91
DFS-14413S	1-5/8 ODF			526	445	93
DFS-14417S	2-1/8 ODF			530	444	99
DFS-14421S	2-5/8 ODF			528	442	106
DFS-19211S	1-3/8 ODF	4	1680	668	587	91
DFS-19213S	1-5/8 ODF			670	589	93
DFS-19217S	2-1/8 ODF			674	588	99
DFS-19221S	2-5/8 ODF			670	584	106

