



## LIQUID INDICATORS

| Drawing | Part number | Connections |             | PS [psi] | TS [°F] |     | Package pcs |
|---------|-------------|-------------|-------------|----------|---------|-----|-------------|
|         |             | SAE Flare   | ODS Ø [in.] |          | Min     | Max |             |


### SAE FLARE MALE - MALE CONNECTIONS

|                                                                                   |         |      |   |     |     |      |    |
|-----------------------------------------------------------------------------------|---------|------|---|-----|-----|------|----|
|  | 3810/22 | 1/4" | - | 500 | -40 | +248 | 20 |
|                                                                                   | 3810/33 | 3/8" |   |     |     |      |    |
|                                                                                   | 3810/44 | 1/2" |   |     |     |      |    |
|                                                                                   | 3810/55 | 5/8" |   |     |     |      |    |
|                                                                                   | 3810/66 | 3/4" |   |     |     |      |    |

### SAE FLARE MALE - FEMALE CONNECTIONS

|                                                                                   |         |      |   |     |     |      |    |
|-----------------------------------------------------------------------------------|---------|------|---|-----|-----|------|----|
|  | 3850/22 | 1/4" | - | 500 | -40 | +248 | 20 |
|                                                                                   | 3850/33 | 3/8" |   |     |     |      | 20 |
|                                                                                   | 3850/44 | 1/2" |   |     |     |      | 20 |
|                                                                                   | 3850/55 | 5/8" |   |     |     |      | 20 |
|                                                                                   | 3850/66 | 3/4" |   |     |     |      | 16 |

### COPPER BRAZE CONNECTIONS

|                                                                                   |        |   |        |     |     |      |    |
|-----------------------------------------------------------------------------------|--------|---|--------|-----|-----|------|----|
|  | 3840/2 | - | 1/4"   | 500 | -40 | +248 | 25 |
|                                                                                   | 3840/3 |   | 3/8"   |     |     |      | 25 |
|                                                                                   | 3840/4 |   | 1/2"   |     |     |      | 25 |
|                                                                                   | 3840/5 |   | 5/8"   |     |     |      | 16 |
|                                                                                   | 3840/6 |   | 3/4"   |     |     |      | 16 |
|                                                                                   | 3840/7 |   | 7/8"   |     |     |      | 21 |
|                                                                                   | 3840/9 |   | 1.1/8" |     |     |      | 16 |

## MOISTURE INDICATORS

| Drawing | Part number | Connections |             | PS [psi] | TS [°F] |     | Package pcs |
|---------|-------------|-------------|-------------|----------|---------|-----|-------------|
|         |             | SAE Flare   | ODS Ø [in.] |          | Min     | Max |             |


### SAE FLARE MALE - MALE CONNECTIONS

|                                                                                     |         |      |   |     |     |      |    |
|-------------------------------------------------------------------------------------|---------|------|---|-----|-----|------|----|
|  | 3910/22 | 1/4" | - | 500 | -40 | +248 | 20 |
|                                                                                     | 3910/33 | 3/8" |   |     |     |      |    |
|                                                                                     | 3910/44 | 1/2" |   |     |     |      |    |
|                                                                                     | 3910/55 | 5/8" |   |     |     |      |    |
|                                                                                     | 3910/66 | 3/4" |   |     |     |      |    |

### SAE FLARE MALE - FEMALE CONNECTIONS

|                                                                                     |         |      |   |     |     |      |    |
|-------------------------------------------------------------------------------------|---------|------|---|-----|-----|------|----|
|  | 3950/22 | 1/4" | - | 500 | -40 | +248 | 20 |
|                                                                                     | 3950/33 | 3/8" |   |     |     |      | 20 |
|                                                                                     | 3950/44 | 1/2" |   |     |     |      | 20 |
|                                                                                     | 3950/55 | 5/8" |   |     |     |      | 20 |
|                                                                                     | 3950/66 | 3/4" |   |     |     |      | 16 |

### COPPER BRAZE CONNECTIONS

|                                                                                     |        |   |        |     |     |      |    |
|-------------------------------------------------------------------------------------|--------|---|--------|-----|-----|------|----|
|  | 3940/2 | - | 1/4"   | 500 | -40 | +248 | 25 |
|                                                                                     | 3940/3 |   | 3/8"   |     |     |      | 25 |
|                                                                                     | 3940/4 |   | 1/2"   |     |     |      | 25 |
|                                                                                     | 3940/5 |   | 5/8"   |     |     |      | 16 |
|                                                                                     | 3940/6 |   | 3/4"   |     |     |      | 16 |
|                                                                                     | 3940/7 |   | 7/8"   |     |     |      | 21 |
|                                                                                     | 3940/9 |   | 1.1/8" |     |     |      | 16 |