

TABLE 1: General Characteristics

Catalogue Number		Connections		Ball Port Ø [mm]	Kv Factor [m³/h]	TS [°C]		PS [bar]	Risk Category according to PED
without access fitting	with access fitting	ODS				min.	max.		
		Ø [in.]	Ø [mm]						
6570/M6	6570/M6A	–	6	10	0,8	-40	+150	45 (1)	Art. 3.3
6570/2	6570/2A	1/4"	–		3				
6570/3	6570/3A	3/8"	–						
6570/M10	6570/M10A	–	10						
6570/M12	6570/M12A	–	12		5				
6570/4	6570/4A	1/2"	–						
6570/M15	6570/M15A	–	15	15	17				
6570/5	6570/5A	5/8"	16						
6570/M18	6570/M18A	–	18						
6570/6	6570/6A	3/4"	–						
6570/7	6570/7A	7/8"	22	19	29				
6570/M28	6570/M28A	–	28	25	51				
6570/9	6570/9A	1.1/8"	–						
6571/5	–	5/8"	16	10	5				
6571/7		7/8"	22	15	17				
6571/M28		–	28	19	29				
6571/9		1.1/8"	–						
6571/11		1.3/8"	35	25	51				

(1) : MWP = 435 psi according to UL approval

